

# MULTIMIG 511

Part #EL900012 with Push-Pull Torch  
Part #EL900011 with Standard Aluminum Torch  
Part #EL900070 with Brazing Torch

***A push-pull torch designed specifically to optimize aluminum welding.***  
***Synergic pulsed welder with full set of welding programs!***

***Welding and brazing of aluminum alloys, galvanized sheet metal, stainless, and high-strength steel.***

The push-pull system has an up-down digital current adjust at your finger tip - enables real-time control of welding process. Programmable options are available to customize the unit operation.

**Features**

- OEM required synergic pulsed technology - includes a complete set of programs
- Inverter technology enables precision control of output power
- **GREEN technology** - Integrated Power Factor Correction (PFC) technology reduces operating costs.

***INCLUDES Built-in cart for easy welder handling and storage for gas cylinder***



#EL900012 with Push-Pull Torch



Push-pull torch



Standard torch



**1-800-445-9262**

[www.chiefautomotive.com](http://www.chiefautomotive.com)

Improve the speed, quality and profitability of every repair you make. Contact your local distributor or call Chief Automotive Technologies today.



©2018 VEHICLE SERVICE GROUP<sup>SM</sup> Printed in the U.S.A. All Rights Reserved. Unless otherwise indicated, CHIEF AUTOMOTIVE TECHNOLOGIES, VEHICLE SERVICE GROUP<sup>SM</sup>, DOVER and all other trademarks are property of the Dover Corporation and its affiliates. Chief reserves the right to alter product specifications and/or package components without notice, excluding changes to components subject to FCC & IC regulations.

**SPECIFICATIONS**

Single Phase Input	230V 50/60Hz + 15% to -20%
Supple Fuse Rating (slow blow)	30A
Input Power	5.7 KVA 20% 4.1 KVA 60% 3.2 KVA 100%
Current Adjustment Range	20A to 200A
Duty Cycle (10 min 40°C) According to IEC 60974.1	200A 20% 140A 60% 120A 100%
Stepless Regulation	Electronic
Standard Supplied Synergic Programs	0.6/0.8/0.9/1.0 Fe, Alu 0.6/0.8/0.9/1.0/1.2 AL 0.8/0.9 Stainless Steel, CuSi3 0.9 Flux core
Max. Wire Spool Size	Ø 200 mm / 5kg Ø 300 mm / 15kg
Protection Class	IP 23 S
Weight	99.2 lbs
Dimensions Inches	18.9 x 33.7 x 32.5h